



INFINITY TIG 225 DC-HF/LIFT VRD 230V



Visão global

INFINITY TIG 225 DC-HF/LIFT VRD 230V

cod. 816089

Máquina de solda inversora TIG (gatilho de alta frequência HF ou LIFT), TIG PULSATO-PULSATO EASY e MMA em corrente contínua (DC).

Características:

- ajuste de múltiplos parâmetros da curva de soldagem TIG
- operação do curso 2/4
- provisão para controle remoto
- dispositivo VRD
- MMA: arc force ajustável e hot start, anti-stick
- várias proteções.

Fornecida com acessórios de soldagem TIG.



MMA DC



1 PH 230V



EAC CERTIFICATION



TIG DC HF/LIFT MMA



CE MARKING

Especificações

CODE	CODE 816089	V ₀	MAX NO LOAD VOLTAGE 82 V	Φ	POWER FACTOR (cosphi) 0,7
V _{1PH}	SINGLE PHASE MAINS VOLTAGE 230 V	A _{MAX}	MAX ABSORBED CURRENT 30 A	D _{DC} MIN/MAX	D. USABLE ELECTRODES IN DC 1,6 - 4 mm
F	MAINS FREQUENCY 50 / 60 Hz	A _{60% MAX}	ABSORBED CURRENT AT 60% - MAX 20 A	IP	PROTECTION DEGREE IP23
A _{MIN} / A _{MAX}	CURRENT RANGE 10 - 200 A	P _{MAX}	MAX ABSORBED POWER 4,7 kW	W/H/L	DIMENSIONS 39 - 15,5 - 29 cm



INFINITY TIG 225 DC-HF/LIFT VRD 230V



MAX CURRENT 200 A - 25 %



ABSORBED POWER AT 60% 3,2 kW



WEIGHT 6 kg



CURRENT AT 60% 120 A



EFFICIENCY 89 %



EAN CODE 800489700604 8